



SEALPACK™ WITH MAXPACKING

Best available technology and most resilient
sootblower packing in the industry

Feed tube packing is one of the most time consuming and labor intensive sootblower component to maintain. Short-lived and unreliable feed tube packing, coupled with the reduction in maintenance resources, has forced the boiler owner to run their sootblowers with leaking feed tube packing. This not only reduces the sootblower cleaning performance and wastes valuable high pressure steam, but also poses a safety hazard for any personnel working around the boiler.

WHAT IS MAXPacking?

MAXPacking was originally designed for a heavy duty sootblower operated in an Integrated Gasification Combined Cycle (IGCC) Syngas Cooler. The IGCC Syngas Cooler generally is operated at a very high pressure ~500 psig (34 bar), which requires the sootblower to

be operated at even higher blowing pressure ~900 psig (62 bar). This heavy duty application demands that the sootblower packing is free from leaks and able to withstand 900 psig blowing pressure even after multiple operations in harsh environment. The success of MAXPacking in IGCC sootblowing application is now being made available for conventional sootblowers used in coal fired and pulp & paper recovery boilers.

MAXPacking for SEALPack™ consists of a Non-Split carbon fiber reinforced sealing ring and 2 high density end rings. The sealing rings are die-formed into a single set with no splits to improve the integrity and performance of the packing. The high density end rings provide a tough leading edge when exposed to condensate and prevent extrusion of sealing rings.

SEALPACK™ WITH MAXPACKING

Rapid Exchange Program for Current SEALPack™ Users

- Discounted price in exchange for the return of the old/used SEALPack™
- Rapid Exchange Part No: RCBA001060-MP
- To purchase SEALPack™ with MAXPacking: CBA001060-MP
- To convert your old SEALPack™ to SEALPack™ with MAXPacking, please inquire about the conversion kit: CBA001060-MP-Kit

Benefits

Most Resilient Sootblower Packing in the Industry

- Lasts 5–10 times longer than regular packing
- Highest performance – Leak free from outage to outage – if combined with ArmorGlide™ Feed Tube

Ease of Maintenance

- No packing re-tensioning needed
- Visual indicator to determine worn packing
- Fast removal & replacement of worn packing by swapping the SEALPack™ cartridge
- Comes with the tools required for easy removal and replacement of the old SEALPack™

Improve Safety

- Longer packing life & easy maintenance features would make it easier for the maintenance team to achieve the goal of eliminating packing leak and improving the safety of all personnel working around the boiler.



Clyde Industries Inc.
4015 Presidential Parkway | Atlanta | GA | 30340
+1 800 241 5996 | clyde-industries.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =